

Cutting Handles



Stock Number	Length	Hose Sizes	Weight	Size Fittings	Cutting Attachments
819-0800	10" (25.4cm)	¼" or 5/16" (.63mm or .79mm)	(Less Tip) 21oz. (.595 kg)	9/16"-18 B Ext.	4800 & 5800 Series

- A versatile torch for a variety of jobs.
- Superior flow for heavy heating.
- Uses all popular fuel gases.
- Heat output can be up to 1,350,000 BTU/hr with MAPP® No. 18 heating tip.
- Spring loaded valves provide smooth torque control and anti-backlash for precise flame control.
- Brass Corn Cob® handle for non-slip grip, stainless steel head.



Stock Number	Length	Hose Sizes	Weight	Size Fittings	Cutting Attachments
818-0750	8 ¾" (22cm)	¼" or 5/16" (.63mm or .79mm)	(Less Tip) 16oz. (.454 kg)	9/16"-18 B Ext.	4700 & 5700 Series

- A versatile torch for welding and heating for use with all popular fuel gases.
- Very good flow capacity.
- Excellent heating capabilities. Can be used with styles 759, 760 multi-flame heating tips.
- Spring loaded valves to provide smooth torque control and anti-backlash for precise flame control.
- Brass Corn Cob® handle for non-slip grip.



Attachments & Handles

Stock Number	Length	Hose Sizes	Weight	Size Fittings	Cutting Attachments
818-0550	8" (20cm)	¼" or 5/16" (.63mm or .79mm)	(Less Tip) 16oz. (.454 kg)	9/16"-18 B Ext.	3590 Series

- Stainless steel ball valves assure positive seating and control.
- Stainless steel torch heads provide better tip seating, less distortion.
- Spring loaded lift type cutting oxygen valve allows fast on-off.
- 32 pitch rack and 1 ¾ Dia Barrel.

