

Advantium *PLUS* Remote Alarms

Features

- Two Input channels (Advantium 2 *PLUS*)
- One Input channel (Advantium 1 *PLUS*)
- Two Output Channels
- Dry contact relay outputs
- Normally-Open or Normally-Closed output capability
- Highly visible lighted status notification
- Distinctive audible notification
- Auto-reset when cylinders are replenished
- Audible Alarm Silence feature
- Ability to “Daisy Chain” multiple alarms
- Switch selectable 40-minute alarm delay
- Convenient on/off switch
- Integrated power supply
- Optional Intrinsic Safety Barriers available for hazardous environments

Specifications

- **Audio**
93db audible alarm
- **Power**
120 VAC or 220 VAC
50/60 Hz
- **Outputs**
2 channels (Advantium 2 *PLUS*)
1 channel (Advantium 1 *PLUS*)
Dry Contacts
Normally-Open/Normally-Closed (jumper selectable)
Contact Rating .5A 24V
- **Inputs**
2 channels
Accepts Normally-Open/Normally-Closed contact closure (selectable)
Resettable fuse protection
- **Connectors**
Input: 6 pin circular
Output: 4 pin circular
- **Dimensions**
4 3/4" h x 7 1/2" w x 2 5/8" d



Ask About Our

EXTENDED
WARRANTY

On This CONCOA Product

Ordering Information

| Series | Description |
|-----------------|---|
| 575-0021-01-000 | Advantium 2 Remote Alarm (120V) |
| 575-0022-01-000 | Advantium 2 Remote Alarm (220V) |
| 575-0011-01-000 | Advantium 1 Remote Alarm (120V) |
| 575-0012-01-000 | Advantium 1 Remote Alarm (220V) |
| 529-5312 | Intrinsic Safety Barriers for 526 and 527 Series Switchover Systems and 529 Protocol Alarm Station |
| 529-5296 | Intrinsic Safety Barriers for 522, 523, 537 Series Switchover Systems |
| 529-5316-XX | Input Cable Assembly available in 3', 10', 25', 50' and 100' lengths. "XX" in stock number denotes length. |
| 529-5329-XX | Interconnect Cable Assembly available in 3', 10', 25', 50' and 100' lengths. "XX" in stock number denotes length. |