DISTRIBUTION ACCESSORIES



HYDRAULIC FLASH ARRESTORS

CONCOA Hydraulic Flash Arrestors are designed to provide flashback control in fuel gas piping systems. Equipped with floor stands and flashback fluid, the equipment protects against common accidents such as reverse flow, flashback, and hose burn. Multiple line size and flow rate options combined with robust materials of construction provide the reliability and safety required in industrial fuel gas systems.





836 0038 Shown

Features 1" or 1-½" Connections Excellent flow capacity

300 or 1000 SCFH max flow rateApplication flexibility

20 PSIG Relief Pressure Safe and reliable control

Materials of Construction

Carbon Steel

Inlet/Outlet Connections
Carbon Steel

Specifications

Maximum Flow at 15 PSIG 300 SCFH (141.6 LPM) 1000 SCFH (471.9 LPM)

Inlet/Outlet Connections

1" MNPT (300 SCFH version) 1-1/2" MNPT (1000 SCFH version)

Relief Pressure 20 PSIG

Weight

55 lbs (300 SCFH version) 123 lbs (1000 SCFH version)

Ordering Information			
Part Number	Gas Service	Inlet/Outlet	Relief Pressure
836 0037	Acetylene	1" MNPT	20 PSIG
836 0038	Acetylene	1-½" MNPT	20 PSIG