PIPELINE REGULATOR ACCESSORIES



FLASHBACK ARRESTORS









Flashback Arrestors can be easily installed on the outlet fitting of most regulators, gas supply points or inline. They help meet ANSI Z49.1:2005, OSHA, and NFPA safety requirements and help protect against the most common causes of accidents such as reverse flow, flashback, and hose burn backs. Each CONCOA flashback arrestor is 100% tested with actual flashbacks and have built in 100-Micron inlet filters, reverse flow check valves (non-return valves), flame barriers, and thermal cut off valves.

Materials & Specifications

UL Listed

Complies with ISO 5175, BAM/DIN 730, BS 6158

Thermal Shut Off


Brass/Temperature sensitive stainless silver solder

Valve Spring

316 stainless steel

Features

- 1. Thermal Shut Off
- 2. Flame Barrier
- 3. Check Valve
- 4. Re-settable Pressure Control
- 5. Inlet Filter



Ordering Information						
Part Number	Service	Regulator End	Hose Connection	Max Pressure	Max Flow	Weight
801 7001	Acetylene Hydrogen LPG	9/16" -18 (B) LH Female	9/16" -18 (B) LH Male	15 PSIG 50 PSIG 50 PSIG	508 SCFH Acetylene (at 15 PSIG) 5213 SCFH Hydrogen (at 50 PSIG) 1100 SCFH LPG (at 50 PSIG)	1.1 oz. (.50 kg)
801 7002	Oxygen	9/16" -18 (B) RH Female	9/16" -18 (B) RH Male	143 PSIG	3745 SCFH (at 143 PSIG)	1.1 oz. (.50 kg)
801 7003	Acetylene Hydrogen LPG	9/16" -18 (B) LH Female	9/16" -18 (B) LH Male	15 PSIG 50 PSIG 50 PSIG	349 SCFH Acetylene (at 15 PSIG) 3308 SCFH Hydrogen (at 50 PSIG) 698 SCFH LPG (at 50 PSIG)	5.25 oz. (.15 kg)
801 7004	Oxygen	9/16" -18 (B) RH Female	9/16" -18 (B) RH Male	143 PSIG	2307 SCFH (at 143 PSIG)	5.25 oz. (.15 kg)
801 7005	Acetylene Hydrogen LPG	9/16" -18 (B) LH Female	9/16" -18 (B) LH Male	15 PSIG 50 PSIG 50 PSIG	508 SCFH Acetylene (at 15 PSIG) 5213 SCFH Hydrogen (at 50 PSIG) 1100 SCFH LPG (at 50 PSIG)	12 oz. (.34 kg)
801 7006	Oxygen	9/16" -18 (B) RH Female	9/16" -18 (B) RH Male	143 PSIG	3745 SCFH (at 143 PSIG)	12 oz. (.34 kg)