

ACCESSORIES



MIXERS

CONCOA gas mixers are used to mix oxy-fuel mixtures in welding and heating applications. These mixers can be used in all oxy-fuel mixes. Mixers are sized for the tip ranges detailed in the table below.



Ordering Information

Part Number	Use w/ Torch	Tip Range	Internal Thread
810 0780	750	00-5	3/8"-20
810 0781	750	0-10	3/8"-20
810 1700	750	0-10	7/16"-20
811 1800	800	00-5	3/8"-20
811 0890	800	0-10	3/8"-20
811 0891	800	11-13	3/8"-20
811 0899 (Jet Mixer)	800	Heating	1/2"-20

HOSES

CONCOA Twin Hoses - Grade T

CONCOA twin line hoses are constructed of high quality, cord-reinforced hose, molded side-by-side into a single, light and flexible unit. They come in 3/16, 1/4, and 5/16 sizes and meet RMA-CGA specifications. End fittings are 9/16-18 RH B on green (Oxygen hose) both ends, and 9/16-18 LH B on Red (Fuel Gas hose) both ends.



TORCHES

Ordering Information

Part Number	Length	Inside Diameter
908 0365-01	25 ft	3/16"
908 0425-01	25 ft	1/4"
908 0575-01	25 ft	5/16"
908 1362-01	12.5 ft	3/16"