

583 SERIES AUTO SWITCH 2



The 583 Series AutoSwitch 2 with stainless steel internals is an electronic gas delivery system for high purity gas service, typically in the laboratory or process plant. It automatically changes cylinder or bank priority from the primary source to a reserve supply without causing pressure fluctuations to the use line. The system comes with inlet pressure transducers to help monitor gas supply pressure. Unlike most fully automatic switchovers, every valve in the AutoSwitch 2 has metal-to-metal seals suitable for continuous high purity gas delivery without compromising purity integrity. The 583 AutoSwitch 2 is intended for high pressure supply sources only. For cryogenic liquid supply systems, CONCOA recommends the IntelliSwitch family of products.

Typical Applications

- High Purity Non-toxic, Non-flammable Gas from High Pressure Supply Sources
- Gas chromatography and Mass Spec Carrier and Support Gases
- Central Gas Supply System for Laboratory, Research, or Process Plants
- Biotech, Pharmaceutical, and Forensic Gas Systems
- Modified Atmosphere Packaging (MAP)



5832011-01-001 shown

Features

Metal-to-Metal Seals prevent possibility of gas contamination

Integral Line Regulator provides stable line pressure during changeover

Variable Line Pressure allows pressure change on site

Microprocessor Control permits fully automatic priority assignment

400 Series Stainless Steel Components with CAPSULE® Seat Technology feature 360° filtration

Primary-Reserve Failure Mode ensures continuous efficient gas supply during power loss

Three 4-20 mA Analog Outputs echo the pressure to optional remote alarm/monitoring system

Leak Detection Capability eliminates waste and improves safety when engaged

Integral Pressure Monitors activate digital relays when inlet or outlet pressures cross user-set limits

Optional Altos 2 Remote Alarm prevents downtime or process interruption

Materials and Specifications

Maximum Inlet Pressure: 3000 PSIG (210 BAR)

Temperature Range: 0°F to 100°F (-18°C to 40°C)

Maximum Flow at 100 PSIG (7 BAR): 600 SCFH (283 LPM)

Inlet Connection: 1/2" FNPT

Outlet Connection: 1/2" FNPT

Priority Valve Body: 316L stainless steel barstock

Line Regulator Body: 316L stainless steel barstock

Helium Leak Integrity: 1×10^{-8} scc/sec

Diaphragms: 316L stainless steel

Enclosure: Polycarbonate (NEMA 12)

Tubing and Fittings: 316L stainless steel

Internal Seals: PTFE

583 SERIES AutoSwitch 2



Materials and Specifications

Seats: PTFE (line regulator); PCTFE (priority regulator)

Transducers: Two 0-6000 PSIG (inlets); One 0-1000 PSIG (outlet)

Power Input: 24VDC 800 mA (high voltage transformer not included)

Outputs: Dry contact relay outputs (four); Normally open/normally closed; Contact rating 0.5A 24V
4-20 mA analog outputs (three)

Weight: 30 lbs. (14 kg)

Conformances: Cleanliness meets or exceeds CGA G-4.1; CRN OH5216.5; CRN: OH17950.5

Ordering Information

A	B	C	D	-CON	Options
583	Outlet Pressure Inlet Connection	Cylinders/Side	Alarm	Hose	Installed Options
1: 0-100 PSIG (0-7 BAR)	0: 1/2" FNPT	0: No inlet connection	1: No alarm included	-001: 1/2" FNPT Port	None
2: 0-200 PSIG (0-14 BAR)	1: 316L Stainless steel manifolds with one 24" (610 mm) stainless steel flexible hose at each station	1: One cylinder	A: Altos 2 Alarm included	<i>Please specify inlet connection (if applicable).</i>	C: Compact manifold connector and 6" extensions
3: 0-350 PSIG (0-24 BAR)	2: 316L Stainless steel manifolds with one 36" (914 mm) stainless steel flexible hose at each station	2: Two cylinders		CGA DIN 477 BS 341 and others available.	
	5: 316L Stainless steel diaphragm valves with one or two 36" (914 mm) stainless steel flexible hoses per side only	3: Three cylinders			
	6: 316L Stainless steel diaphragm valves with one or two 72" (1829 mm) stainless steel flexible hoses per side only	4: Four cylinders			
	7: 316L Stainless steel double row manifold with two 24" (610 mm) stainless steel hoses at each station	5: Five cylinders			
	8: 316L Stainless steel double row manifold with two 36" (914 mm) stainless steel hoses at each station	6: Six cylinders			
		7: Seven cylinders			
		8: Eight cylinders			

Related Options



Part No.	Description
835 5703	Power supply for 583 Series AutoSwitch 2 (100-240VAC to 24VDC 800mA)

583 SERIES AutoSwitch 2



Installation Dimensions

Formula to Calculate Overall Length:



A = Distance from CL of Outlet to CL of Valve 1
 B = Distance from CL of Last Valve to End Cap
 S = Distance Between Valves
 OAL = System Overall Length

$OAL = (A + B + [S \times \{\text{number of valves minus 1}\}]) \times 2$


Example 1 4 Valves Per Side, Standard Manifolds (12" Spacing):

$OAL = (16.866 + 2.524 + [12.000 \times 3]) \times 2 = 110.78 \text{ in} [2814 \text{ mm}]$

Example 2 8 Valves Per Side, Compact Manifolds (6" Spacing):

$OAL = (11.676 + 2.524 + [6.000 \times 7]) \times 2 = 112.40 \text{ in} [2855 \text{ mm}]$

Wall Mounting Dimensions:




◆ 1/4" Female NPT Relief Valve Port

★ 1/2" Female NPT Port


* Electrical Input via Pierceable Water-Tight Hole Plugs in ø.540 in [ø13.5 mm] Holes on Top and Bottom of Enclosure.

Power Supply Sold Separately.

Wall Mount Ears Horizontal



Wall Mount Ears Vertical




Each mounting ear is independently rotatable to either the vertical or the horizontal position.

583 SERIES AutoSwitch 2



Piping and Installation Diagram

582 & 583 Series AutoSwitch 2



LEGEND	
	Electronic Circuit Board
	Pressure Transducer
	Pressure Gauge
	Pressure Reducing Valve, Adjusting Screw Operated
	Pressure Reducing Valve, Preset
	Pressure Reducing Valve, Hand Operated
	Electric Motor, 24 VDC
	Mechanical Coupling
	Limit Switch, Low Pressure
	Limit Switch, High Pressure
	Relief Valve
	NPT Port